

## tek vue

## value & simplicity

Tek Vue<sup>TM</sup> is a glass office-front system that responds to the essential needs of today's workplace. The system focuses on single-center glazing and thin-profile frames, while providing effortless integration with conventional construction and existing Teknion wall programs.

Tek Vue wall and door programs are built on the concept of a universal platform, which re-envisions how a system can be specified, planned and installed within the evolving world of interior architecture.

## features

### value through simplicity

• Tek Vue offers the essential elements; a single-center glass wall program and pared down, yet progressive, pivot and barn door program. The system is easy to install, uses materials efficiently and offers flexibility in specification.

## small footprint, large application

- Tek Vue is optimized to integrate with conventional building construction as well as Altos and Focus programs to satisfy budget or performance requirements.
- Thin wall and door profiles take up little real estate and respond to varying building conditions through effective site accommodation. Tek Vue also offers a comprehensive articulating and electrical program, as well as variable angle fascia capabilities.

## universal platform

- Tek Vue framing elements are universal in nature to streamline on-site staging and accelerate installation procedures.
- Pivot and barn door frames are not specific to individual door leafs, hardware or ceiling heights, thereby allowing easy placement anywhere on the floor-plan.
- All wall and door framing elements are cut on site from common lengths, allowing flexibility with any on-site discrepancies.







# specifications

#### sizing

- Ceiling heights from 86" 120" high in  $\frac{1}{16}$ " increments
- Fascia widths 12"- 48" in <sup>1</sup>/<sub>16</sub>" increments
- Base and ceiling frame 1 3/8" thick by 2 3/8" nominal height
- Horizontal frame cut to length on site up to lengths of 121"

### building accommodation

- Ceiling adjustment range: + 3/4", 3/4"
- Floor adjustment range: + 1/2", 1/4"
- Wall start adjustment range:  $+\frac{1}{4}$ ",  $-\frac{1}{4}$ " (min.)

#### fascia offering

• Single-centered glass only

#### door offering

- Universal Pivot and Barn door frames
- Frameless, Framed and Solid Pivot door
- Frameless Glass Barn door
- Single Leaf only

### glass options

- 10 and 12mm seamless glass
- Tempered and Laminated
- Clear and Low Iron finishes

#### electrics

- Low profile electrics program
- Hard-wired

#### integration

- Drywall/base building
- Altos, Focus